

# KTM/Husqvarna Adjustable Length Pull-Rod Instructions for Use



858-586-1100 · info@luxonMX.com · LuxonMX.com · @LuxonMX

**Please read carefully as this is vital to the performance of your new parts!**

- 1) Despite what other companies may try to tell you, there is no one-size-fits-all pull-rod length! Each rider is different: different weights, heights, skill levels, etc., and each will prefer a different length pull-rod. For this reason, we've made our pull-rods adjustable in length. If you try it at one length and don't like it, all you have to do is adjust it and try again. You can't do that with a non-adjustable "performance link" from our competitors!
- 2) Luxon pull-rods assemble similarly to the stock pull-rods with the exception of the adjustable length feature. Refer to your service manual for the standard installation instructions and fastener torque values. The pull-rods are adjustable in length using eccentric inserts. Six total inserts are included: three matching sets. Each matching set of inserts has a flat insert and a stepped insert (to stop rotation of the bolt head when tightening) and can be rotated for a different length.



- 3) Inserts are identified by different numbers of dots on each end, and the pull-rod length is determined by the laser etched arrow pointing to the dots. Refer to the chart below for the resulting length at different adjustment positions. The image above shows the insert installed with the arrow pointing to one dot, which results in a 148.2 mm long pull-rod.

Dots	Length (mm)	Ride Height Change (mm)	Notes
0	147.2	3.0 Taller	
1	148.2	0.0	2016+ Stock Length
2	149.2	3.1 Lower	Luxon Recommended Starting Position
3	150.2	6.1 Lower	
4	152.2	9.0 Lower	
5	152.2	12.0 Lower	

- 4) We recommend starting at 149.2 mm (2 dots). Ride the bike and adjust longer or shorter to find what works best for you. A longer length will lower the rear of the bike and slightly decrease the progressiveness of the linkage curve. Remember to reset your sag every time you make a length adjustment. You also might need to vary fork heights in the triple clamps depending on your setup goals.

## ----- WARNING -----

Luxon MX products are designed for closed course competition only, and do not comply with federal motor vehicle safety standards. Luxon MX products may not be used on public roads, streets, highways, or freeways. Installation of this product must be performed by a trained professional. Failure to follow the installation instructions and perform routine maintenance can result in injury or death. There are no guarantees associated with Luxon MX products and Luxon MX product is to be used at your own risk. Luxon MX, its staff, owners, employees, contractors, and associates are NOT responsible for use of this product, or its installation, and may not be held liable for any damages that occur.